



# Cleaning Agent 761.0

**Hot melt for cleaning melting units, hoses, and application units in which reactive PUR hot melt adhesives are processed.**

## Fields of application

- Cleaning of melting and application units with changeable inserts from reactive PUR hot melt adhesives and other non-reactive hot melt adhesive systems (e.g. EVA basis)

## Advantages

- The use of a hot melt cleaning agent prevents clogging of feeding systems as well as reactive incrustations of application units. Nozzles are maintained unclogged.

## Properties of the cleaning agent

<b>Base:</b>	EVA-Copolymers
<b>Specific gravity:</b>	approx. 0.98 g/cm <sup>3</sup>
<b>Colour:</b>	mahogany, ref. 70
<b>Viscosity</b>	
<b>Brookfield HBTD</b>	
<b>Sp. 27/10 rpm:</b>	
at 120°C	approx. 110.000 mPa · s
at 140°C	approx. 55.000 mPa · s
at 160°C	approx. 28.000 mPa · s
at 180°C	approx. 17.000 mPa · s
<b>Supplied as:</b>	granules, on request in cartridges and pouches
<b>Identification:</b>	Identification not required according to the German hazardous substances regulations GefStoffV (see our safety data sheet)

When hot melt adhesives are melted and applied, vapours are set free and an unpleasant odour can occur, even if the recommended working temperature has been observed. Moreover if the prescribed working temperature is exceeded over a longer period, harmful decomposition products can develop. Precautions should be taken to eliminate the vapours, e.g. by using a suitable ventilation system.

## Application techniques

When PUR hot melt adhesives are used, the application units, especially those with nozzles, have to be completely cleaned with the nozzles filled during periods of machine standstills (e.g. at night or on weekends) or whenever the systems are changed. This can easily be done by means of feeding and melting the hot melt cleaning agent.

## Attention!

Before PUR hot melt adhesives are again used in these machines the hot melt cleaning agent 761.0 has to be drained off completely.

## Packaging

Paper bag, 20.00 kg net  
Carton containing 12 aluminium cartridges, 0.25 kg net each  
Carton containing 6 aluminium tins, 0.20 kg net each  
Carton containing 4 aluminium tins, 1.50 kg net each  
Special metal pails, 15.00 kg net

## Storage

KLEIBERIT Cleaning Agent 761.0 can be stored for approx. 2 years. Keep in a cool and dry place.

EX 1101, replaces former data sheets



**Waste Disposal**

Disposal of contents and/or containers should comply with all applicable federal, state and local regulations.

Our containers are made of recyclable material.

**Service**

Our application department may be consulted at any time without obligation. The statements made herein are based on our experience gained to date. They are to be considered as information without obligation. Please test and establish for yourself the suitability of our products for your particular purposes. No liability exceeding the value of our product can be derived from the foregoing statements. This also applies to the technical consultancy service which is rendered free of charge and without obligation.