



194 CANDLEWOOD RD.
BAY SHORE, NY 11706
800-644-6449
631-434-2775 FAX
WWW.EDGECOINC.COM

Data Sheet PWG Backing Fleece 23ST/20

EdgeCo Manufactures and Distributors

Properties:

Backing Fleece

23ST/20 is a glue impregnated fleece which is pressed onto veneer by heat reactivation of the glue. The pressing process is done by means of fleece backing machines and the application of additional glue onto the veneer.

Fleece Carrier

Component: cellulose and polyester fibers, acrylic binder
Grammage: 23 g /sq meter (tolerance + or - 2g / sq mete)

Coating:

Basis: polyvinyl acetate (PVAc)
Grammage: 20 g /sq meter (tolerance + or - 2g / sq meter)

Storage:

Conditions: dry storage, protect against water and humidity
Temperature: ideally room temperature, by short-term up to 50° C.
Shelf Life: up to 12 months.

Form of Delivery

Packing: In rolls on Pallets
Roll Length: 2,000 linear meters
Inside Diameter: 75mm
Outside Diameter: approx. 450mm

All data is based on PWG's own experience, measuring and test results. It is not a guarantee for any properties. When considering the huge number of different materials and processing conditions is not possible to assume any liability from this data sheet as well as from our technical advice. We recommend making your own tests so you can evaluate that the fleece type is suitable for your application. Therefore all advice in this data is without any liability.

PWG Veneerbackings Gmbh – Aichener Strasse 8 – Bayern – Germany - 86877